


PIN ASSIGNMENT

NO	SYMBOL
1	RS
2	R/W
3	E
4	DB0
5	DB1
6	DB2
7	DB3
8	DB4
9	DB5
10	DB6
11	DB7
12	VSS
13	VDD
14	V0

NOTE:

- 1, GENERAL TOLERANCE: ±0.2.
- 2, (...) IS REFERENCE DIMENSION.
- 3, COMPLY ROHS.
- 4, * CRITICAL DIMENSION.



DETAIL: DOTS (4:1)

Display Type	FSTN
	POSITIVE
	TRANSFLECTIVE
Front Polarizer	
Operating Method	1/16 DUTY,1/5 BIAS
Viewing Angle	12 O'CLOCK
LCD Driver IC	ST7036I
Operating Voltage	VDD=5.0V VLCD=5.0V
Operation Temperature	0°C TO 50°C
Storage Temperature	-10°C TO 70°C
Interface	
Backlight	

					DRAWN	CL	TITLE	DRAWING NO.			
					ME.CHECKED	XB					
					EE.CHECKED	YY					
					PE.CHECKED						
					APPROVED	LDK	MODULE SPEC.	UNIT	mm	SCALE	FIT
01		first issue		CL	09.07.29	CUSTOMER'S APPROVAL		3rd Angle		SHEET 1 OF 1	
VER.	SYMBOL	AMENDMENT		SIGN	DATE		TRUEVISION TECHNOLOGIES LTD				