



PIN ASSIGNMENT

NO.	SIGNAL
1	GND
2	V5
3	VDD
4	RS
5	R/W
6	E
7	D0
8	D1
9	D2
10	D3
11	D4
12	D5
13	D6
14	D7

- NOTE:
1. GENERAL TOLERANCE: ± 0.2 .
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. RoHS COMPLIANT

Display Type	FSTN POSITIVE TRANSFLECTIVE
Front Polarizer	
Operating Method	1/16 DUTY, 1/5 BIAS
Viewing Angle	12 O'CLOCK
LCD Driver IC	NT7605H-BDT01
Operating Voltage	VDD=5.0V
Driver Voltage	VLCD=5V
Operation Temperature	-20°C TO 70°C
Storage Temperature	-30°C TO 80°C
Interface	
Backlight	

					DRAWN	yc	TITLE	DRAWING NO.			
					EE.CHECKED	HJB	MODULE SPEC.	STR-TC1093			
					ME.CHECKED	WYL		UNIT	mm	SCALE	FIT
					APPROVED	GLP		3rd Angle		⊕	SHEET 1 OF 1
01		First Issue		yc	11.01.24	CUSTOMER'S APPROVAL	BOM NO.: BM110124-03	TRUEVISION TECHNOLOGIES LTD			
VER.	SYMBOL	AMENDMENT		SIGN	DATE						