


PIN NO.	DIFINATION
1	VDD0
2	VDD1
3	SI
4	RSX
5	CSX
6	SCL
7	NC
8	RES
9	LED+
10	LED-
11	VSS
12	VSS

UNFOLDED SHIPMENT

- NOTE:
1. GENERAL TOLERANCE: ±0.2.
  2. (<...> IS REFERENCE DIMENSION.
  3. \* CRITICAL DIMENSION
  4. COMPLYABLY RoHS.



Panel	Display Type	a-Si TFT, TRANSMISSIVE
	Viewing Angle	12 0'CLOCK(Peak CR) 6 0'CLOCK(Good View)
LCM	Driver IC	ST7735S
	Interface	SPI
	Operating Voltage	VDD1=2.8V VDD0=1.8V
	Luminance	TBD
	Center CIE coordinate	TBD
	Backlight unit	WHITE(3.2V,15mA)
	Connector type	Soldering
	Storage Temp.	-30°C TO 80°C

VER.	SYMBOL	AMENDMENT	SIGN	DATE	CUSTOMER'S APPROVAL	DRAWN	LH	TITLE	DRAWING NO.
01		First Issue	LH	2015.5.5				MODULE SPEC.	STR-TF0319DT014
									UNIT mm SCALE FIT
									3rd Angle  SHEET 1 OF 1
									TRUEVISION TECHNOLOGIES LTD.