


PIN FUCTION	
PIN	SYMBOL
1	VLED-
2	VLED+
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	CLKIN
31	STBYB
32	HSD
33	VSD
34	DEN
35	NC
36	GND
37	XR(NC)
38	YD(NC)
39	XL(NC)
40	YU(NC)

NOTE:
 1. GENERAL TOLERANCE: ±0.2.
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLIABLY RoHS.



Display Type	TFT
Viewing Angle	NORMALLY WHITE, TRANSMISSIVE
LCD Driver IC	12:00 CLOCK
Operating Voltage	HX8664B+HX8264D
Operation Temperature	VDD=3.3V
Storage Temperature	-20°C TO 70°C
Interface	-30°C TO 80°C
Backlight	24bit-RGB
Surface luminance	12-LED WHITE
White X/Y	250cd/m2(TYP) 40MA/19.2V
	X:0.32±0.05 Y:0.36±0.05

						TITLE	DRAWING NO.
						TFT MODULE SPEC.	TF7302DT050
							UNIT mm SCALE FIT
							3rd Angle SHEET 1 OF 1
01	FIRST ISSUE	LH	2014.11.20	CUSTOMER'S APPROVAL		TRUEVISION TECHNOLOGIES LTD	
VER.	SYMBOL	AMENDMENT	SIGN	DATE			