



TFT PIN ASSIGNMENT

1	LDE-A
2	LED-A
3	LED-K
4	LED-K
5	GND
6	VCOM
7	DVDD
8	MODE
9	DE
10	VS
11	HS
12~19	B7~B0
20~27	G7~G0
28~35	R7~R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D
41	VGH
42	VGL
43	AVDD
44	RESET
45	NC
46	VCOM
47	DITHB
48	GND
49	NC
50	NC

NOTE:

1. GENERAL TOLERANCE: ± 0.3 .
2. (...) IS REFERENCE DIMENSION.
3. * CRITICAL DIMENSION
4. COMPLYABLY RoHS.

Panel	Display Type	7.0" TFT/TRANSMISSIVE BOE
	Viewing Angle	6 0' Clock (Recommended 12 0' Clock)
LCM	Driver IC	TBD
	Interface	RGB
	Operating Voltage	VCC=3.3V
	Luminance	400TYP
	Center coordinate	--
	Backlight	WHITE(9.9V,140mA)
	Connector type	ZIF(FH28-50S-0.5SH)
	Operation Temp.	-20°C TO 70°C
Storage Temp.	-30°C TO 80°C	

					DRAWN	LH	7.0 TFT	DRAWING NO.				
					CHECKED			STR-TF7306DDT070	UNIT	mm	SCALE	FIT
					APPROVED				3rd Angle		SHEET	1 OF
01		first issue	LH	2014.4.16	CUSTOMER'S		TRUEVISION TECHNOLOGIES LTD					
VER.	SYMBOL	AMENDMENT	SIGN	DATE	APPROVAL							