



- NOTE:
1. GENERAL TOLERANCE:  $\pm 0.3$ .
  2. (...) IS REFERENCE DIMENSION.
  3. \* CRITICAL DIMENSION
  4. COMPLIABLY RoHS.

PIN ASSIGNMENT

PIN	SYMBOL	PIN	SYMBOL
1	VLED+	26	G1
2	VLED+	27	G0
3	VLED-	28	R7
4	VLED-	29	R6
5	GND	30	R5
6	VCOM	31	R4
7	DVDD	32	R3
8	MODE	33	R2
9	DE	34	R1
10	VS	35	R0
11	HS	36	GND
12	B7	37	DCLK
13	B6	38	GND
14	B5	39	L/R
15	B4	40	U/D
16	B3	41	VGH
17	B2	42	VGL
18	B1	43	AVDD
19	B0	44	RESET
20	G7	45	NC
21	G6	46	VCOM
22	G5	47	DITHB
23	G4	48	GND
24	G3	49	NC
25	G2	50	NC

Panel	Display Type	7.0" TFT/TRANSMISSIVE
	Viewing Angle	ALL
	Driver IC	ILI5120-9G/ILI6150C-9G
LCM	Interface	RGB
	Operating Voltage	VCC=3.3V
	Luminance	150typ
	Center coordinate	-----
	Backlight	WHITE(9.8V,140mA)
	Connector type	ZIF(FH28-40S-0.5SH)
	Operation Temp.	-20°C TO 70°C
Storage Temp.	-30°C TO 80°C	

					DRAWN	LH	DRAWING NO.				
					CHECKED		STR-TF7308CDI070				
					APPROVED						
01	first issue		LH	2015.6.10	CUSTOMER'S APPROVAL		UNIT	mm	SCALE	FIT	
VER.	SYMBOL	AMENDMENT	SIGN	DATE			3rd Angle		SHEET 1 OF 1		
							TRUEVISION TECHNOLOGIES LTD				