



1	VCC
2	IOVCC(1.8V)
3	INABLE
4	RESET
5	HSYNC
6	VSYNC
7	DOTCLK
8	CS
9	SDI
10	SCL
11	SDO
12~35	D00~D23
36	GND
37	XL
38	YD
39	XR
40	YU
41	GND
42	LEDA
43	LEDA
44	LEDK
45	LEDK

NOTE:

1. GENERAL TOLERANCE: ±0.3.
2. (...) IS REFERENCE DIMENSION.
3. * CRITICAL DIMENSION
4. COMPLYABLY RoHS.
5. FPC CONNECTOR: FH23-45S-03SHW(05).

A~~~|||||~~~K

If=20mA, Vf=2.6~3.3V

B/L CIRCUIT DIAGRAM

Panel	Display Type	3.5" TFT/TRANSMISSIVE
	Viewing Angle	U/D/L/R 60/50/60/60
	Driver IC	ILI9805C
LCM	Interface	RGB
	Operating Voltage	VDD=3.3V
	Luminance	110(MIN),140(TYP)
	Center coordinate	(0.29,0.32)
	Backlight	WHITE(32V,20mA)
	Connector type	ZIF(FH23-25S-03SHW(05))
	Operation Temp.	-20°C TO 70°C
Storage Temp.	-30°C TO 80°C	

					DRAWN	WKL	TITLE	DRAWING NO.			
					CHECKED	LXY	MODULE SPEC.	STR-TF7354CRT035			
			WKL	14.06.06	APPROVED	PXH	BOM No:	UNIT	mm	SCALE	FTT
			WKL	14.05.28				3rd Angle		SHEET 1 OF 1	
01		first issue	WKL	14.05.22	CUSTOMER'S APPROVAL		TRUEVISION TECHNOLOGIES LTD				
VER.	SYMBOL	AMENDMENT	SIGN	DATE							