



LCD Main_FPC	
PIN	NAME
1	GND
2	VDDIO
3	GND
4	VDD
5	IO_RD
6	IO_WRX
7	IO_DCX
8	IO_CSX
9	IO_RESX
10	GND
11	DB7
12	DB6
13	DB5
14	DB4
15	DB3
16	DB2
17	DB1
18	DB0
19	LEDA
20	LEDK

Panel	Display Type	TFT, TRANSMISSIVE
	Viewing Angle	ALL
	Driver IC	ST7789V
LCM	Interface	MCU 8BIT
	Operating Voltage	VDDIO=2.8V VDD=2.8V
	Luminance	380TYP
	Center coordinate	/
	Backlight	2 LED 20mA/LED
	Connector type	/
	Operation Temp.	-20°C TO 70°C
Storage Temp.	-30°C TO 80°C	

- NOTE:
1. GENERAL TOLERANCE: ±0.20.
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLIABLY RoHS.

					DRAWN	LH	TITLE	DRAWING NO.			
					ME.CHECKED		MODULE SPEC.	STR-TF7399ADT015			
					EE.CHECKED			UNIT	mm	SCALE	FIT
					PE.CHECKED			3rd Angle		SHEET 1 OF 1	
					APPROVED						
01		First Issue		LH	2015.10.9	CUSTOMER'S APPROVAL	TRUEVISION TECHNOLOGIES LTD				
VER.	SYMBOL	AMENDMENT		SIGN	DATE						