



DOT DETAIL
SCALE 20:1

NO.	SIGNAL	NO.	SIGNAL
1	V0	16	DB6
2	V1	17	DB5
3	V2	18	DB4
4	V3	19	DB3
5	V4	20	DB2
6	C4+	21	DB1
7	C2-	22	DB0
8	C2+	23	E-RD
9	C1+	24	RW-WR
10	C1-	25	RS
11	C3+	26	RESETB
12	VOUT	27	CS1B
13	VDD		
14	VSS		
15	DB7		

Display Type	FSTN POSITIVE REFLECTIVE
Operating Method	1/65 DUTY 1/9 BIAS
Viewing Angle	6:00
LCD Controller/Driver	ST7565R
Logic Voltage (V)	3.3V
LCD Driving Voltage	8.9V
Operation Temperature	0°C TO 50°C
Storage Temperature	-20°C TO 70°C
Backlight	None
Interface	8080-8bit

- NOTE:
1. GENERAL TOLERANCE: ±0.2.
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLYABLY RoHS.

					DRAWN	YC	TITLE	DRAWING NO.			
					ME.CHECKED	YC	MODULE SPEC.	STR-TG0621C			
					PE.CHECKED	WYL	BOM NO:	UNIT	mm	SCALE	FIT
					APPROVED	YB		3rd Angle		SHEET 1 OF 1	
01		First issue		YC	08.06.05	CUSTOMER'S APPROVAL	TRUEVISION TECHNOLOGIES LTD				
VER.	SYMBOL	AMENDMENT		SIGN	DATE						