



PIN ASSIGNMENT

NO.	SIGNAL	NO.	SIGNAL
1	NC	19	NC
2	NC	20	V0
3	/CS	21	XV0
4	/RES	22	NC
5	AO	23	NC
6	/WR(R/W)	24	NC
7	/RD(E)	25	VG
8	DO	26	NC
9	D1	27	NC
10	D2	28	NC
11	D3	29	NC
12	D4	30	NC
13	D5	31	NC
14	D6	32	C86
15	D7	33	P/S
16	VDD	34	NC
17	VSS	35	NC
18	NC	36	NC


- NOTE:
- 1, GENERAL TOLERANCE: ±0.2.
 - 2, (...) IS REFERENCE DIMENSION.
 - 3, COMPLY ROHS.
 - 4, * CRITICAL DIMENSION.



DOTS DETAIL (10:1)



COM&SEG LAYOUT



Backlight:

Display Type	FTN
	POSITIVE
	TRANSFLECTIVE
Operating Method	1/65 DUTY,1/9 BIAS
Viewing Angle	6 O'CLOCK
LCD Driver IC	ST7567
Operating Voltage	VDD=3.3V VLCD=9.5V
Operation Temperature	-20°C TO 70°C
Storage Temperature	-30°C TO 80°C
Interface	Parallel 68/80 8Bit
Backlight	YELLOW-GREEN

				DRAWN	ZJJ/09.5.11	TITLE	DRAWING NO.			
				ME.CHECKED	XB/09.5.11	MODULE SPEC.	STR-TG0830A			
				EE.CHECKED	YZK/09.5.11		UNIT	mm	SCALE	FIT
				PE.CHECKED	DB/09.5.11		3rd Angle	⊕		SHEET 1 OF 1
				APPROVED	LD/09.5.11		TRUEVISION TECHNOLOGIES LTD.			
01	First issue	ZJJ	09.4.13	CUSTOMER'S APPROVAL						
VER.	SYMBOL	AMENDMENT	SIGN	DATE						