



PIN	SYMBOL
1	PS0
2	PS1(PS2)
3	/CS
4	RST
5	A0
6	RW_WR
7	E_RD
8	D0
9	D1
10	D2
11	D3
12	D4
13	D5
14	D6
15	D7
16	VDD
17	VSS
18	NC
19	NC
20	NC
21	NC
22	NC
23	NC
24	NC
25	NC
26	K(RED)
27	A
28	K(BLUE)

Display Type	FSTN POSITIVE TRANSFLECTIVE
Front Polarizer	
Operating Method	1/128 DUTY,1/12 BIAS
Viewing Angle	6 O'CLOCK
LCD Driver IC	ST7571
Operating Voltage	VDD=3.0V
Driver Voltage	VOUT=11.85V
Operation Temperature	0°C TO 50°C
Storage Temperature	-10°C TO 60°C
Interface	SERIAL&PARALLEL
Backlight	BLUE&RED(10mA)

- NOTES:
1. GENERAL TOLERANCE: ±0.2.
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. RoHS COMPLIANT.
 5. Use high-transmission transfective polarizer

					DRAWN	leihui	TITLE	DRAWING NO.			
					CHECKED	LXY	MODULE SPEC.	STR-TG3067			
					APPROVED	PXH		UNIT	mm	SCALE	FIT
01		initial issue	DAIXIN	10.09.10	CUSTOMER'S APPROVAL			3rd Angle		SHEET 1 OF	1
VER.	SYMBOL	AMENDMENT	SIGN	DATE			TRUEVISION TECHNOLOGIES LTD.				