



NOTE:
 1. GENERAL TOLERANCE: ±0.2.
 2. (..) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLYABLY RoHS.

DISPLAY TYPE	FSTN
	POSITIVE
	TRANSFLECTIVE
FRONT POLARIZER	NORMAL
OPERATING METHOD	1/128 DUTY
	1/11 BIAS
OPERATION VOLTAGE(VOP)	12.9V
VIEWING ANGLE	12:00
OPERATION TEMPERATURE	-20°C TO 70°C
STORAGE TEMPERATURE	-30°C TO 80°C
CONNECTOR TYPE	PIN
LCD CONTROLLER/DRIVER	UC1617WGAB
BACKLIGHT	WHITE,12.0±0.2V,40mA

					DRAWN	CCX	10.06.22	TITLE	DRAWING NO.			
					CHECKED	ZJ	10.06.22	MODULE SPEC.	STR-TG50028			
					APPROVED	DCW	10.06.22		PROJECT NO.	S50028	VER.	01
									UNIT	mm	SCALE	FIT
01		First Issue		CCX			10.03.22		3rd Angle		SHEET 1 OF 1	
VER.	SYMBOL	AMENDMENT		SIGN	DATE	CUSTOMER'S APPROVAL		TRUEVISION TECHNOLOGIES LTD				