




PIN	ASSIGNMENT
1	VSS
2	VLCD
3	VS+
4	VS-
5	VB0-
6	VB1-
7	VB1+
8	VB0+
9	VDD
10	VSS
11	CS0
12	CD
13	RST
14	D6
15	D7
16	VSS

- NOTE:
1. GENERAL TOLERANCE:  $\pm 0.2$ .
  2. (...) IS REFERENCE DIMENSION.
  3. \* CRITICAL DIMENSION
  4. COMPLY R0HS.



Display Type	FSTN
	POSITIVE
	TRANSMISSIVE
Front Polarizer	
Operating Method	1/60 DUTY, 1/10 BIAS
Viewing Angle	6 O'CLOCK
LCD Driver IC	UC1698u
Operating Voltage	VDD=3.0V
Driver Voltage	VLCD=14.0V
Operation Temperature	-10°C TO 60°C
Storage Temperature	-20°C TO 70°C
Interface	4-SPI
Backlight	WHITE(30mA, 5.5--7.0V)

			chenliang	10.08.12					
01		First Issue	CL	10.01.25					
VER.	SYMBOL	AMENDMENT	SIGN	DATE	CUSTOMER'S APPROVAL				
						DRAWN	FJ	TITLE	
						CHECKED	XB YY	DRAWING NO.	
						APPROVED	LDK	STR-TG6015A	
								UNIT	mm
								SCALE	FIT
								3rd Angle	SHEET 1 OF 1
						TRUEVISION TECHNOLOGIES LTD			