


NOTE:

- 1、UNIT: mm;
- 2、VDD: I<1mA, V: 2.8V;
- 3、Operating Temp.: -20--+70°C;
- 4、Storage Temp: -30--+80°C;
- 5、LCD:STN, yellow green, positive, transmissive, 6: 00, 1/65D, 1/9B, Vlcd: 9.0 V;
- 6、Backlight: White, Side light, voltage:3.3V,
- 7、RoHS;
- 8、unspecified tolerance: ±0.2



14	NC		
13	VLCD	LCD driving voltage output	RTD
12	VB1+	voltage pump	
11	VB1-	voltage pump	C1
10	VBO-	voltage pump	
9	VBO+	voltage pump	C2
8	GND	ground	
7	VDD	LCD voltage	
6	LCD_DATA	Serial data signal	
5	LCD_CLK	Serial clock signal	
4	NC		
3	LCD_A0	Command or data selection	
2	LCD_RST	Reset	
1	CS	LCD chip select	
NO	SYMBOL	FUNCTION	

				DRAWN	ZJZ	10.01.05	TITLE MODULE SPEC.	DRAWING NO. STR-TG8133			
				ME.CHECKED	LZX	10.01.05		PROJECT NO.	VER.	04	
				EE.CHECKED	XHB	10.01.05		UNIT	mm	SCALE	FIT
				PE.CHECKED	DJ	10.01.05		3rd Angle		SHEET 1 OF 1	
				APPROVED	LG	10.01.05					
01	First Issue			ZJZ	09.10.20	CUSTOMER'S APPROVAL	TRUEVISION TECHNOLOGIES LTD				
VER.	SYMBOL	AMENDMENT		SIGN	DATE						