



PIN ASSIGNMENT	
PIN	NAME
1	VSS
2	A0
3	WR
4	RD
5	XCS
6	RESET
7	VDD
8	D0
9	D1
10	D2
11	D3
12	D4
13	D5
14	D6
15	D7
16	K
17	NC
18	A

Display Type	FSTN(W/B) POSITIVE TRANSFLECTIVE
Front Polarizer	
Operating Method	1/160 DUTY, 1/10 BIAS
Viewing Angle	6 O'CLOCK
LCD Driver IC	UC1698u
Operating Voltage	VDD=3.3V VLCD=16.5V
Operation Temperature	-30°C TO 70°C
Storage Temperature	-40°C TO 80°C
Interface	8080 Parallel
Backlight	WHITE LED (I=60 mA, 5V)

						DRAWN EE.CHECKED ME.CHECKED APPROVED	YC HJB WYL DXH	TITLE MODULE SPEC. BOM NO.:BM130327-01A	DRAWING NO. STR-TG9163				
01		first issue		YC	13.03.28	CUSTOMER'S APPROVAL			UNIT 3rd Angle	mm	SCALE	FIT	SHEET 1 OF 1
VER.	SYMBOL	AMENDMENT	SIGN	DATE				TRUEVISION TECHNOLOGIES LTD					