



NO.	SIGNAL
1	VG
2	XV0
3	V0
4	VDD
5	VSS
6	CS0
7	A0
8	ERD
9	RWR
10	RST
11	D0
12	D1
13	D2
14	D3
15	D4
16	D5
17	D6
18	D7
19	K
20	A



NOTE:
 1. GENERAL TOLERANCE: ±0.2.
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLYABLY RoHS.

Display Type	FSTN
	POSITIVE
	TRANSFLECTIVE
Front Polarizer	NORMAL
Driving Method	1/65 DUTY,1/9 BIAS
Viewing Direction	12 O'CLOCK
LCD Driver IC	ST7525
Logic Voltage (V)	3.0V
LCD Driving Voltage	8.8V
Operation Temperature	-15°C TO 60°C
Storage Temperature	-30°C TO 85°C
Interface	8080 SERIES
Backlight	WHITE If=20mA Vf=15.5±2.0V

VER.	SYMBOL	AMENDMENT	SIGN	DATE	DRAWN	ZC	TITLE	DRAWING NO.			
01		First issue	LJW	13.09.06			MODULE SPEC.	STR-TG9195			
							BOM NO.:BM130806-01A	UNIT	mm	SCALE	FIT
								3rd Angle			SHEET 1 OF 1
							TRUEVISION TECHNOLOGIES LTD.				