



NO.	SIGNAL	NO.	SIGNAL
1	/CS	19	CAP1-
2	/RES	20	CAP1+
3	A0	21	CAP2+
4	WR/(RW)	22	CAP2-
5	RD/(E)	23	CAP4+
6	DB0	24	VRS
7	DB1	25	V1
8	DB2	26	V2
9	DB3	27	V3
10	DB4	28	V4
11	DB5	29	V5
12	DB6	30	VR
13	DB7	31	C86
14	VDD	32	P/S
15	VSS	33	HPM
16	VOUT	34	IRS
17	CAP5+		
18	CAP3+		

- NOTE:
1. GENERAL TOLERANCE: ±0.2.
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLYABLY RoHS.

Display Type	FSTN POSITIVE REFLECTIVE
Operating Method	1/65 DUTY 1/9 BIAS
Viewing Angle	6:00
LCD Controller/Driver	ST7565P
Logic Voltage (V)	3.0V
LCD Driving Voltage	9.6V
Operation Temperature	-20°C TO 70°C
Storage Temperature	-30°C TO 80°C
Humidity Test Condition	
Interface	8080/6800/SPI-4

VER.	SYMBOL	AMENDMENT	SIGN	DATE	DRAWN	LJW	TITLE	DRAWING NO.				
							MODULE SPEC.	STR-TG9229				
					ME.CHECKED	MWW		BOM NO.:BM131218-01A	UNIT	mm	SCALE	FIT
					EE.CHECKED	MWW			3rd Angle			
					APPROVED	HJB		SHEET 1 OF 1				
01		Frist Issue	LJW	13.12.21	CUSTOMER'S APPROVAL		TRUEVISION TECHNOLOGIES LTD					