


17	D7	1	LEDR
18	VDD	2	LEDG
19	VSS	3	LEDB
20	V1	4	IF2
21	V2	5	IF1
22	V3	6	/RST
23	V4	7	/CS
24	V0	8	/WR
25	CAP1N	9	A0
26	CAP3P	10	D0
27	CAP1P	11	D1
28	CAP2P	12	D2
29	CAP2N	13	D3
30	CAP4P	14	D4
31	VLCD	15	D5
32	CAP5P	16	D6



DISPLAY TYPE	TN
	POSITIVE
	TRANSMISSIVE
FRONT POLARIZER	NORMAL
OPERATING METHOD	1/4 DUTY
	1/3 BIAS
OPERATION VOLTAGE	VDD=3.3V VDP=10.4V
VIEWING ANGLE	12:00
LCD Driver IC	ST7049
OPERATION TEMPERATURE	0°C TO 70°C
STORAGE TEMPERATURE	-20°C TO 70°C
CONNECTOR TYPE	FPC
BACKLIGHT COLOR	/

NOTE:
 1. GENERAL TOLERANCE: ± 0.20 .
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. RoHS COMPLIANT

					DRAWN	ZQ	TITLE	DRAWING NO.			
					EE.CHECKED	TJP	MODULE SPEC.	STR-TG9234			
					PE.CHECKED	TJP		UNIT	mm	SCALE	FIT
					APPROVED	HJB		3rd Angle		SHEET	1 OF 1
01		first issue		zq	14.01.06	CUSTOMER'S APPROVAL	BOM NO.:	TRUEVISION TECHNOLOGIES LTD			
VER.	SYMBOL	AMENDMENT		SIGN	DATE						