



PIN ASSIGNMENT

NO.	SIGNAL	NO.	SIGNAL
1	NC	14	D6
2	NC	15	D7
3	CS1B	16	VDD
4	RSTB	17	VSS
5	A0	18	VOUT
6	RWR	19	V4
7	ERD	20	V3
8	D0	21	V2
9	D1	22	V1
10	D2	23	V0
11	D3	24	C86
12	D4	25	PSB
13	D5	26	NC

- NOTE:
1. GENERAL TOLERANCE: ±0.20.
 2. (<...>) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLY R0HS.



DISPLAY TYPE	DFSTN NEGATIVE TRANSMISSIVE
FRONT POLARIZER	
OPERATING METHOD	1/65DUTY,1/9BIAS
DRIVER VOLTAGE	VDD=3.0V
OPERATION VOLTAGE	VDP=9.0V
VIEWING ANGLE	6:00
OPERATION TEMPERATURE	-20°C TO 70°C
STORAGE TEMPERATURE	-30°C TO 80°C
CONNECTOR TYPE	FPC
INTERFACE	
LCD CONTROLLER/DRIVER	ST7565R
BACKLIGHT COLOR	

					DRAWN	LJW	TITLE MODULE SPEC. BOM NO.: BM140109-12A	DRAWING NO. STR-TG9239			
					EE.CHECKED	MWW		UNIT	mm	SCALE	FIT
					PE.CHECKED	MWW					
					APPROVED	HJB		TRUEVISION TECHNOLOGIES LTD.			
01		First issue	LJW	14.01.20	CUSTOMER'S APPROVAL						
VER.	SYMBOL	AMENDMENT	SIGN	DATE							