


PIN ASSIGNMENT

PIN	NAME
1	VG
2	V0
3	XV0
4	VM
5	VSS
6	SDA
7	SCL
8	RESB
9	CSB
10	VDDA
11	VDDI



COM & SEG LAYOUT

- NOTE:
 1. GENERAL TOLERANCE: ±0.20.
 2. (.) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLIABLY RoHS.
 5. ACF for CDG of IC: CP6920F3(3um Filler).
 6. ITO Glass With Hard Coat at both sides.

DISPLAY TYPE	FSTN POSITIVE TRANSFLECTIVE
FRONT POLARIZER	—
OPERATING METHOD	1/80DUTY,1/10BIAS
DRIVER VOLTAGE	VDD=3.3V
OPERATION VOLTAGE	VOP=10.0V
VIEWING ANGLE	6:00
OPERATION TEMPERATURE	-20°C TO 80°C
STORAGE TEMPERATURE	-25°C TO 85°C
CONNECTOR TYPE	FPC
INTERFACE	—
LCD CONTROLLER/DRIVER	ST7527 SPI-3
BACKLIGHT COLOR	—

					DRAWN	LJW	TITLE	DRAWING NO. STR-TG9281			
					EE.CHECKED	TJP	MODULE SPEC.	CUSTOMER NO.			
					PE.CHECKED	TJP		UNIT	mm	SCALE	FIT
					APPROVED	HJB		3rd Angle		SHEET 1 OF 1	
01		First issue		LJW	14.05.10	CUSTOMER'S APPROVAL	BOM NO.: BM140327-06A	TRUEVISION TECHNOLOGIES LTD.			
VER.	SYMBOL	AMENDMENT		SIGN	DATE						